

CLAIM

1) Shock-absorbing means of attachment for components and printed circuit and component support
5 board, characterised by the fact that it has at least two ends (EX), each of which is equipped with an opening (O) and/or an internal or external thread (FI, FE) and characterised by the fact that the part or parts located
10 (PS) once the means of attachment according to this invention is installed in an attachment position between two separate objects.

*Do not
enter
A19*

PCT FR 03 002066 . ENTER INTO THE USPTO NATIONAL PHASE
INTERNATIONAL FILING DATE : 03 JULY 2003
PRIORITY DATE CLAIMED : 02 AUGUST 2002
NAME OF SOLE INVENTOR : COISSAC Bruno

ENGLISH LANGUAGE TRANSLATION OF THE AMENDMENTS
TO THE CLAIMS AND THE DECLARATION UNDER PCT ARTICLE 19
2 pages.

DECLARATION selon l'article 19.1

Une fois Le moyen de fixation selon l'invention installé en situation de fixation, aucune pièce rigide ou combinaison de pièces formant un ensemble rigide ne relie les deux extrémités (EX) aménagées chacune pour la fixation à un objet distinct.

DECLARATION in accordance with article 19.1

Once the means of attachment according to the invention is installed in an attachment situation, no
5 rigid part or combination of parts forming a rigid assembly links the two ends (EX) each equipped for attachment to a separate object.